



# SKY3000

## Portable gas detector



SKY3000

Portable gas detector

SK Y3000 series is a high-perFormance portable gas detector that can detect multiple gases (Oxygen compounds VOC, combustible gas and toxic gas) at the same time and has man down alarm Function. The device has humanized operation Functions such as one-key security detection, one-key storage, automatic image Flipping, as well as the man down alarm Function; With optionalBluetooth transmission Function, allowing saFety personnel to obtain real-time data and the alarm status. It has obtained international IECEx, ATEX explosion-proof certiFication and Chinese explosion-proof certiFication; As it passed the antistatic test, and the protection level reaches IP67; With saFer product design and the module designwhich makes the detection Faster, and the compact ergonomic designmakes the device easy carrying; What's more, the device is also a suction and diFFusion dual-purpose instrument. The instrument is mainly working in suction mode. When the air pump Fails or in special emergency situations, it can automatically switch to the diFFusion sampling method, thereby improving the protection to a new Level.

The explosion-proof Grade oF the SKY3000 series is Ex ia IIC T4 Ga, which is applicable to the explosive gas mixture zone 0, zone 1, and zone 2 oF the Factory with grades IIA, IIB, and IIC and temperature group T1~T4.



## Specialized in Gas Detection For 16 Years

### Product Advantage

#### Rugged and durable

- The instrument can effectively resist a three-meter drop
- The protection level of the instrument reaches IP67
- The instrument has passed the EMC anti-static interference test and can work normally in the walkie-talkie environment

#### Explosion-proof circuit design, safe and reliable

- The instrument has got IECEx, ATEX, Chinese explosion-proof certificates and the explosion-proof level reaches Exia IIC T4 Ga

#### Multiple security protection

- The man down alarm Function has upgraded the safety of underground operators
- Password protection Function prevents non-operators from modifying menu parameters
- With safety reminder Function, sound and light vibration alarm Function, let operators work without worries
- The high and low alarm latched Function allows the operator to better capture the sudden change of the gas concentration value

#### Simultaneous measurement of multiple gases, multiple numerical display

- The instrument can detect 1-5 gases at the same time
- Real-time value, TWA, STEL, MAX, MIN multiple numerical display





## Large screen display, flexible detection system, multiple filtering devices

- The screen can be automatically turned 180 degrees, which is convenient For viewing in special operating environments
- Built-in powerFul sampling pump, Fast detection speed
- Can be connected 20m sampling tube externally, which is convenient For long-distance or conFined space detection
- Pump suction and diFFusion dual use, to provide operators with more reliable protection
- With a water trap Filter, it can eFFectively Filter water, oil, dust and other impurities. It can also be used in harsh industrial environments such as coal mines and petroleum Fields


## Powerful function, more user-friendly operation

- BeautiFul and Friendly user interFace, reasonable and easy-to-use interactive mode
- Optional Bluetooth Function, data can be transmitted to the mobile phone or PC in real time
- Standard storage Function, one-click data export, convenient For users to analyze
- Unique modiFiable ID identiFication Function, convenient For users to allocate and manage the instrument
- A Full range oF automatic detection Functions, automatic prompts For voltage, pump Failure alarms, etc., more comFortable to use One-key security detection
- one-key open storage, automatic image Flip
- Support PPM and mg/m3 gas unit switch, the concentration value is automatically converted by the system
- Support each channel sensor to restore the Factory setting separately
- Support multi-language including English.Chinese and etc.

## Product specifications

Sampling method	pump suction & diFFusion dual-use type
Gas type	PH3
Principle	Electrochemistry
Measure range	0-10ppm
Resolution	0.01 ppm
Response time	≤30 seconds
Precsiion	≤ ± 2%F.S except For special gases
Language	Chinese/English (More language can be customized)
Automatically test and calibrate aFter power-on	Including reset, maximum value (MAX), minimum value (MIN), STEL, TWA value
Unit	PPM and mg/m3 can be switched and displayed by one key, and the concentration value is automatically converted by the system
Disaply	monochrome graphics (160 x96) ,screen can be automatically Flipped
Backlight	The backlight time can be manually set, and will be turned on automatically when an alarm is issued
Data record	Can store 100,000 sets data, the storage interval is adjustable From 5 to 3600 seconds, data can be exported, with data cable
Alarm	95dB buzzer (@30cm), vibration alarm and Flashing red LED and alarm status indication on the screen, alarm latched; diagnostic alarm and battery undervoltage alarm, pump block alarm; man down alarm, with early warning and optional real-time remote Bluetooth notiFication Function



Battery	3.7V rechargeable lithium battery, battery capacity 2200mA
Working hours	More than 15 hours in continuous pumping mode
Charger	Travel charger with DC interFace, charging time ≥ 4 hours
Explosion-proof grade	IECEEx: Ex ia IIC T4 Ga     ATEX:  II 1G Ex ia IIC T4 Ga
CertiFication (EU regulations)	2004/34/UE (ATEX)
Protection grade	IP68
Working temperature	-20°C~+50°C
Humidity	0~90%RH (no condensation)
Environmental pressure	86~106Kpa
Size	157*84.5*59.5mm (including back clip/water trap Filter) (length * width * height)
Weight	365g (including battery, belt clip and Filter)

Normal gas types and paramaters (Other gases are not listed can be customized)

Detected gas	measure range	Optional ranges	Resolution	Response time
Flammable gas (EX)	0-100%LEL	0-100%VOL	0.1%LEL/0.1%VOL	≤10S
Oxygen (O2)	0-30%VOL	0-25%VOL	0.01%VOL/0.1%VOL	≤10S
Carbon monoxide (CO)	0-1000ppm	0-2000ppm	0.1ppm/1ppm	≤10S
Hydrogen sulfide (H2S)	0-100ppm	0-1000ppm	0.01ppm/0.1ppm	≤10S
Ammonia (NH3)	0-100ppm	0-200ppm	0.01ppm/0.1ppm	≤10S
Chlorine (CL2)	0-10ppm	0-100ppm	0.01ppm/0.1ppm	≤10S
Hydrogen Chloride (HCL)	0-20ppm	0-100ppm	0.01ppm/0.1ppm	≤10S
Nitric oxide (NO)	0-100ppm	0-250ppm	0.01ppm/0.1ppm	≤10S
Nitrogen dioxide (NO2)	0-20ppm	0-100ppm	0.01ppm/0.1ppm	≤10S
Formaldehyde (CH2O)	0-10ppm	0-50ppm	0.01ppm/0.1ppm	≤10S
Ozone (O3)	0-10ppm	0-100ppm	0.01ppm/0.1ppm	≤10S
Carbon dioxide (CO2)	0-2000ppm	0-100%VOL	1ppm/0.01%VOL	≤10S

Product configuration

Standard accessories:

- Gas detector 1 piece
- 12V/1A DC power adapter 1 piece
- USB cable 1 piece
- User manual 1 piece
- warranty card 1 piece
- Filter 1 piece
- Aluminum suitcase 1 piece





## Application



▲ Petrochemical & Chemical Industry



▲ Municipal Engineering & Utilities



▲ Agricultural & Environmental Protection



▲ Electronic



▲ Food & Pharmaceutical Industry



▲ Other Industries

## Project Cases



◀ SKY3000  
used in coal mines

▼ SKY3000  
used in sewers and  
underground areas



SKY3000  
applied in Oil & Gas industries like  
Shell or Petros

SKY3000  
applied in conFined spaces like  
warehouse, ships, Factories,ect.





## More Application

---

- Furniture, Floor, Wallpaper, Coating, Gardening, Interior Decoration and Renovation, DyestuFF, Papermaking, Pharmacy, Health Care, FoodstuFF, Antiseptic.
- DisinFection, Chemical Fertilizer, Resin, Adhesive, Pesticide, Raw Material, Sample, Technological Process, Livestock Farm, ReFuse Processing Plant, Perm Place.
- Bio-pharmaceutical Plant, Green Household, Livestock Breeding, Green House Cultivating, Warehouse Logistics, Brewing And Fermentation, Agricultural Production.

JBK FHU Bogusław Kliś  
39-120 Sędziszów Młp.  
ul. Piaskowa 52  
tel: (+48) 535 416 380